



Salt spray test: 48h – UNI ISO 9227.

TECHNICAL CHARACTERISTICS

- | | | |
|-------------------------------------|--------------------|---|
| 1) RING | Material: | Steel EN 10270-1-SM-2,00 Z (C72) |
| 2) PONTICELLO | Material: | DX51D +AZ 150 UNI EN 10215 (Aluzink B 500 A) |
| 3) SCREW exagon
screwdriver head | Material: | Steel C21 B KB UNI 7356 hardened and tempered |
| | Surface treatment: | Trivalent galvanising Fe/Zn 5 II |

MODEL	ASSEMBLING D Max. (mm.)	TIGHTENING D Min. (mm.)	SCREW (mm.)	Tightening couple MAX. (N/m)
FM- 4942	49	42	L= 40	2
FM- 5245	52	45	L= 40	
FM- 5547	55	47	L= 40	
FM- 5850	58	50	L= 40	
FM- 6557	65	57	L= 40	
FM- 6860	68	60	L= 40	
FM- 7062	70	62	L= 40	
FM- 7264	72	64	L= 45	
FM- 7468	74	68	L= 45	
FM- 7768	77	68	L= 45	
FM- 7971	79	71	L= 40	
FM- 8274	82	74	L= 45	
FM- 8476	84	76	L= 45	
FM- 8780	87	80	L= 45	
FM- 9082	90	82	L= 45	
FM- 10193	101	93	L= 45	
FM- 10395	103	95	L= 45	
FM- 137129	137	129	L= 45	